



# 04000A Motor Oil 10W-40 Super High Performance Diesel Truck

Document version: May 13, 2024



## Description

This high-grade semi synthetic motor oil has been specially developed for diesel engines of commercial vehicles. In addition this motor oil has been formulated to make long oil-change intervals possible and to prevent bore polishing.

## According to the specifications of

ACEA B3 / B4 / E7  
API CF-4 / CG-4 / CH-4 / CI-4  
Allison C4  
Cummins CES 20076 / CES 20077 / CES 20078  
Detroit Diesel 93K215  
Deutz DQC III-10  
Global DHD-1  
JASO DH-1  
MAN M 3275  
MB 228.3  
MTU Type 2  
Mack EO-M Plus / EO-N  
Renault RLD / RLD-2  
Volvo VDS-3

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
04020A	20 L	1	30
04060A	60 L	1	6
04205A	205 L	1	2
04999A	1000 L	1	-
P04000A	1 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.867	kg/l
Viscosity	10W-40	
Kinematic Viscosity at 40°C	86	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	13.1	mm <sup>2</sup> /s
Viscosity Index	153	
Dynamic Viscosity at -25°C	5900	mPa.s
Flashpoint COC	243	°C
Pourpoint	-42	°C
Total Base Number	11.9	mgKOH/g
Sulphated Ash	1.9	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.