



# 86000C Coolant Premium Longlife -40°C G12+ Ready to Use

Document version: May 13, 2024



## Description

This Long Life OAT silicate-free coolant is of very high quality and has been specially developed for protection of non-ferrous metals such as aluminium and magnesium. This coolant is ready to use.

## According to the specifications of

ASTM D3306  
DAF 74002  
Fiat 9.55523  
Ford ESE-M97B49-A / WSS-M97B44-C / WSS-M97B44-D  
GM/Opel 1940 656 / 6277M  
MAN 248 / 324 SNF  
MB 326.3  
Paccar 74002  
Renault 41-01-001  
VW TL 774D G12+ / 774F G12+  
Volvo No. 260 / VCS

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
86001C	1 L	6	450
86005C	5 L	4	112
86020C	20 L	1	30
86060C	60 L	1	6
86205C	205 L	1	2
86999C	1000 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density at 20°C	1.057	kg/l
Colour	red	
Frost Protection	-40	°C
Boiling Point	108	°C
Copper Corrosion	3	

These characteristics are typical of current production. Variations in these characteristics may occur.